







7300 Slim Cover AR Arm





DORMA By Choice™



DORMA 7300 SERIES

Applications:

The 7300 Series is designed to provide a highly flexible door control system suitable for use on all hollow metal, aluminum, and wood doors typically used in commercial construction. It is available in fixed spring sizes: 2, 3, 4. and 5. Doors may be mounted with either ball bearing hinges or pivots. Special brackets and other adapting hardware are available with the 7300 Series product.

Listings & Approvals:

- ANSI Grade 1.
- UL and ULC.
- UL10C for positive pressure.
- UBC 7.2 1997.
- CSFM.
- M.E.A.

Warranty: 25 Years.

Range of Door Sizes:

- Exterior door widths to 42" (1067 mm).
- Interior door widths to 48" (1219 mm).
- Door heights to 96" (2438 mm).
- Door weights to 200 pounds (91 kg).

Finishes:

- Standard Sprayed Finishes:

Aluminum: 689.

Bronze: 691 (Dull), 690 (Statuary), or

695 (Dark Duranodic).

Gold: 696. Black: 693.

- Custom Painted Finishes:

Submit sample. Customer approval required.

Special Application Assistance:

Please contact our Technical Services team at 800-523-8483 if you have any questions or need assistance in developing a custom application.

Closer Mounting Options (based on arm selection):

- Regular pull side of the door.
- Top jamb push side of the door.
- Parallel arm on push side of door.

ANSI A156.4 Grade 1 Selector Chart

Arm(s)	Hingeside	Parallel Arm	Top Jamb
AR	C02011	C02021	C02041
FH	C02051	C02061	C02081
FT4 Function Options	A, D	A, D	A, D

Arm Functions:

- Regular, Top Jamb or Parallel Arm.
- Friction hold-open.

Closer Functions:

- Adjustable back check intensity.
- Adjustable sweep speed.
- Adjustable latch speed.

Cover Options:

- Optional slim plastic cover.

Contact Information:

DORMA Architectural Hardware Dorma Drive, Drawer AC Reamstown, PA 17567-0411

Tel: 800-523-8483 Fax: 800-274-9724

Email: archdw@dorma-usa.com

A DORMA Group Company

www.dorma-usa.com