

SL30SGL

Mini Electronic Side Load Lock



Advantages at a glance:

- Assist with door alignment
- Automatic deadbolting providing high security
- Easily converts from Fail Safe to Fail Secure
- Versatile Installation

The SL30SGL mini electronic side load lock, is a motor driven electronic lock designed to secure commercial and residential single acting doors. Its small footprint ensures the SL30SGL mini can be installed in most locations however it still has the ability to pull a door in tightly against a seal and will release instantly when requested, even with excessive load on the door.

Door Alignment

- Door misalignment of up to 8mm is corrected

Side Load Release

- The door can have in excess of 600kg being applied and it will still release instantly when requested

High Security

- Automatic deadbolting
- 10,000N holding force (1,000kg)
- 10mm thick stainless steel bolt pin

Electronic Convenience

- Input voltage from 12VDC – 24 VDC
- Less than 50mA standby current
- Reverse polarity and transient protection
- Multiple attempts to lock

Simple Configuration

- Convert from Fail Safe to Fail Secure by repositioning a single jumper

Dual Monitoring

- Door and bolt position monitors

Versatile Installation

- Mortise mount horizontally or vertically, on single acting doors
- Surface mount with the aid of the accessories, including mounting onto glass

Physical dimensions

- 160mmL x 30mmW x 51mmD

Flexible design



Surface mounting a lock and/or strike with the aid of the accessories offers more flexibility in installation and makes securing glass doors possible.

Dress plates are offered to give a 'clean' finish when a housing has been installed onto glass. The housing and dress plate are supplied with selfadhesive tape for instant application to glass doors and frames.

Technical data

Lock – Field convertible - SL30SGL

- 160L x 30W x 51D(mm)

Long Strike - SLA213H

- 160L x 30W x 14D(mm)

Housing - SLA214J

- 163L x 34W x 55D(mm)

Dress Plate - SLA216J

- 165L x 0.7W x 58D(mm)

Holding Force

- 10,000N (1000Kg)

Door Misalignment

- Up to 8mm

Side Load Release

- Up to 600Kg opening load on door

Voltage at Lock

- 12 – 24VDC +/-15%

Current Usage

- Holding:
40mA@12VDC, 25mA@24VDC
- Operating:
<250mA@12V, <200mA@24V
- Initial power up:
0.75A@12VDC, 0.4A@24VDC

Monitors Switches

- Bolt position: 30VDC,0.1A
- Door Position: 100VDC, 0.5A

Endurance

- 1,000,000 cycles normal operation

Certifications

- EN 61000-6-1: 2007, EN 61000-6-3:2007
- RoHS Compliant
- FCC Part 15, Subparts A and B
- Fire test of 4 hours certified to BS 476-22:1987
- EN 14846
- EN 1634-1

Subject to technical changes.
11/2024

Any questions? We would be happy to advise you.

Contact us on: +41 44 818 90 11