

QED300

Exit devices



Features

- **More options.** No matter what sort of light commercial application you work with, the QED300 series' wide range of device types, trim selections, and enhanced security features allow the configuration you need.
- **Backed by a leading warranty.** Each QED300 product comes with a lifetime mechanical warranty and a three-year warranty on finish.
- **Reliable safety.** The QED300 series is BHMA/ANSI Grade 1 certified, and significantly exceeds performance requirements. The series includes a thru bolt design for enhanced security and durability.
- **Easy installation.** The QED300 series comes non-handed and field reversible, and are also field sizeable to fit non-standard doors.
- **Short lead time.** QED300 exit devices are available for immediate shipment.

Uncompromised value

When your application calls for reliable quality and durability, dormakaba's QED300 standard-duty exit device series fills the need. For light commercial applications, including wood, steel, or aluminum doors, the QED300 line offers the same quality and robust construction you expect from dormakaba, at a great value.

Flexibility to simplify the job

We designed our QED300 series to fit a wide variety of applications and configuration requirements—giving you the flexibility you need to select features when you order. dormakaba makes it easy to get the job done.



QED300 Standard duty exit device specifications

Certifications	ANSI/BHMA A156.3 Series—Grade 1 ANSI A117.1 Section 404.2.6 Accessibility Code (ADA compliant) UL/cUL listed (3 hour) for "A" label door applications (8' by 8') California Administrative Code Title 24 compliant for Sierra and Summit lever trims	
Materials and options	Rim latch bolt: stainless steel 3/4" (19mm) throw SVR and CVR latch bolt: 1/2" (12.7mm) throw on top latch; 3/8" (9.53mm) on bottom latch Fasteners: wood and machine screws standard, sex bolts optional (standard on fire-rated device) Head cap and end cap: zinc die-cast Escutcheons: dummy, passage, keyed, night latch Dogging: hex key and cylinder dogging available Rim strikes: stainless steel body with plated steel roller standard fire-rated stainless steel strike, with stainless steel roller standard on QED313 SVR and CVR strikes: Top and bottom standard and fire-rated strikes - unfinished	
Sizing and measurements	36" field sizeable to 32" door 48" field sizeable to 36" door Standard door thickness: 1 3/4" (44.5mm) Can accommodate doors up to 2 3/4" thick with use of Thick Door Kit SVR and CVR door height: 7' standard with 84" rod; 8' optional with 96" rod Rim stile width: 3 7/8" (98mm) minimum SVR stile width: 3 1/2" (89mm) minimum CVR stile width: 3 1/2" (89mm) minimum Standard backset: 2 1/4" (57mm) to face of doorstep	
Keying	Keyway options include: BF-SFIC "F", KW-Kwikset, WE-Weiser, SC-Schlage, GA-Yale, LA-Sargent, LC-Less Cylinder	
Exit device functions	QED311: Rim Hex Dog QED312: Rim Cylinder Dog QED313: Rim Fire-rated QED314: SVR Hex Dog QED315: SVR Cylinder Dog	QED316: SVR Fire-rated QED317: SVR Less Bottom Rod – Hex Dog QED318: SVR Less Bottom Rod – Cylinder Dog QED319: SVR Less Bottom Rod – Fire-rated
Finishes	689: Painted Aluminum, 690: Painted Duranodic Bronze	
Warranties	Lifetime mechanical, three-year finish	



689: Painted Aluminum



690: Painted Duranodic Bronze

© dormakaba 2025 Information on this sheet is intended for general use only. dormakaba reserves the right to alter designs and specifications without notice or obligation.

Any questions? We would be happy to advise you.

Contact us at: 1-800-523-8483