

QCL200

Cylindrical locks



Features

- **Designed for security.** With features like thru bolt design, iclutching mechanisms, and fire-rated latches—plus available hurricane compliant option—QCL200 series locks ensure the utmost security.
- **Backed by a leading warranty.** The QCL100 lock series comes with lifetime mechanical, three-year finish, and one-year electrical warranties.
- **Durable safety.** We designed the QCL200 series with heavy-duty torsion springs to prevent lever sag and ensure long-term durability. Each lock in the series is BHMA/ANSI Grade 2 certified.
- **Easy to retrofit.** Choose locks with a SFIC option or keep your existing small format cores and use them with QCL200 series locks. Standard door prep and the same thru bolt pattern found in other common locks makes retrofit quick and easy.
- **Simple to install.** Compartmentalized packaging makes QCL200 locks easier to install.
- **Reliable value.** The QCL200 series combines premium materials, construction, and performance at a great value—both in your up-front investment and in long-range durability.
- **Short lead time.** QCL200 series locks are available for immediate shipment.

A better solution for standard-duty applications

QCL200 standard-duty cylindrical lock series provides a better solution for light commercial applications. Designed for quick installation, easy retrofit, longer performance life, and vandal resistance, the QCL200 series offers a better initial value and significant long-term savings. Our QCL200 series cylindrical locks combine quality, performance, and value—and are backed by the name more people trust with their security.

Simple to customize, install, and retrofit

We designed the QCL200 series to simplify standard-duty solutions. With a range of configuration options, a compatible door prep and bolt pattern, and simplified packaging, a QCL200 series lock makes your job easier.



QCL200 Standard duty cylindrical lock specifications

Certifications	ANSI/BHMA A156.2 Series—Grade 2 ANSI A117.1 Accessibility Code (ADA compliant) UL/cUL listed (3 hour) for "A" label single door applications (4' by 8') UL10C/UBC 7-2 (1997) positive pressure rated UL10B pressure rated California State Reference Code (formerly Title 19 – Fire Marshal) Hurricane Compliant – Miami DADA N.O.A.	
Product specifications	Exposed trim: pressure cast zinc, plated to match finish designation Standard door thickness: 1 3/8" (35mm) – 2" (51mm) Backset: 2 3/4" (70mm) square standard; 2 3/8" (60mm) and 5" (127mm) available Strike: ANSI strike 1 1/4" (32mm) x 4 7/8" (124mm) standard; other options available Door prep: 2 1/8" (54mm) diameter cross bore Latch bolt: keyed/exterior 1/2" (12.7mm) steel throw; interior 1/2" (12.7mm) spring latch; 3/4" throw option for hurricane compliance or fire-rated double door applications Latch faceplate: 1 1/8" (29mm) x 2 1/4" (57mm) standard	
Keying	6-pin non-IC brass cylinders 6- or 7-pin SFIC option available Two keys per lockset Keying options include: master keying, grand master keying, construction keying Keyway options include: BF-SFIC "F", KW-Kwikset, WE-Weiser, SC-Schlage, GA-Yale, LA-Sargent, LC-Less Cylinder	
Functions	ANSI F75	QCL220 Single Dummy
	ANSI F111	QCL230 Passage
	ANSI F76	QCL235 Communicating
	ANSI F109	QCL240 Privacy
	ANSI F109	QCL250 Entry/Office
	ANSI F90	QCL251 Entry/Office SFIC
	ANSI F90	QCL254 Corridor
	ANSI F84	QCL255 Corridor SFIC
	ANSI F84	QCL260 Classroom
	ANSI F86	QCL261 Classroom SFIC
	ANSI F86	QCL270 Storeroom
		QCL271 Storeroom SFIC
Finishes	605: Bright Brass, 613: Oil Rubbed Bronze, 619: Satin Nickel, 625: Bright Chrome, 626: Satin Chrome	
Warranties	Lifetime mechanical, three-year finish (613 carries no finish warranty), one-year electrical	




605 Bright Brass



613 Oil Rubbed Bronze



619 Satin Nickel



625 Bright Chrome



626 Satin Chrome

© dormakaba 2025 Information on this sheet is intended for general use only. dormakaba reserves the right to alter designs and specifications without notice or obligation.

Any questions? We would be happy to advise you.
Contact us at: 1-800-523-8483