

# T900

## Grade 2 tubular locksets

Standard levers



LG



LC



LR



LD



LN



LT

Premium Levers (may require additional lead time)



LA



LF



LV



L109



L110



L112



L113




L114



L117



L118



LTT910 LAB

Interior applications

- Hotel Guest Rooms
- High-End Apartments
- Condominiums
- Office Buildings
- Home Offices

Certification/Compliance

- OPTIONAL—UL/CUL 3 hour fire rated (T910 & T925 only)
- Meets IBC/A117.1 and ADA requirements for accessibility

Warranty

Three (3) year limited warranty.

Exposed trim

Brass, bronze, or stainless steel; B style (2-9/16" diameter) rose and D style decorative rose available.

Finishes

- Brass—605 PVD (Bright), 606 PVD (Satin).
- Bronze—612 PVD (Satin) or 613 PVD (Dark Oxidized Satin).
- Nickel—619 PVD (Satin)
- Chrome—625 (Bright) or 626 (Satin)
- Stainless—629 (Bright) or 630 (Satin)

**Note:** Consult factory for finishes not shown.

Handing

Nonhanded (some lever designs are handed – RH/LH).

Door thickness

1-3/8" to 1-3/4" standard.

Backset

2-3/8" or 2-2/4" available.

Latch face

1" or 1-1/8" available.

Strike

T-strike standard; ANSI or full lip available.

Features

- All DORMA T900 Series locks feature lever designs matching the M9000 mortise locks.
- Easy to install in both wood or hollow metal doors with ANSI/BHMA A156.115 preparations for bored locks (no through-bolting).
- T900 Series lever trims include special auxiliary support springs to ensure smooth operation and long life.
- High-end, coordinating tubular companion to the DORMA M9000 mortise lock.
- Optional fire rated latch available.
- Nonhanded design (some lever designs are handed).
- Nonhanded design (some lever designs are handed).

Functions:

ANSI	DORMA	Description
F75	T910	Passage/closet
F111	T925	Exit/communicating passage
F76	T940	Privacy, bedroom or bath
—	T901	Single sided dummy, through-bolted
—	T902	Double sided dummy



dormakaba USA quality and environmental management systems in Indianapolis, are certified to ISO 9001:2008 and ISO 14001:2004.