

# dormakaba Terminal 97 00

## Time recording and more



Mobile Access



CardLink



### Advantages at a glance

- Secure and simple data recording
- 7" touchscreen with brilliant display and robust glass screen
- Configurable user interface
- Configurable audio booking response (also as language output)
- Supports common RFID media
- Integration of biometric identification and verification solutions
- Multimedia support and individual apps thanks to HTML5
- Compatible with former terminal series
- CardLink
- Integrated microphone
- Integrated loudspeaker
- Optional camera system
- "1-click installation"
- Optional function for bookings with smartphone

### Versatile, multi-functional and customisable

The all-rounder with its modular upgradability represents modern and easy attendance recording as well as intelligent access management and targeted staff communication. Even multimedia contents like training films and staff info can be integrated without difficulty.

The user interface can be freely configured. You can adapt the display to your corporate identity, featuring your own background images, colours, apps and (multimedia) content. The terminal not

only ensures effective attendance recording but, thanks to the standby functionality, is also energy-efficient. You can book with an RFID medium, with the finger or with the smartphone.

### For your needs:

#### Our option packages

We offer the terminal 97 00 in three different variants.

With the 97 20 option package, you get an entry-level device that provides you with all the functions you need for reliable time recording in your company.

The option package 97 40 also enables the connection of standalone door components via CardLink as well as alternative booking with a smartphone.

Option package 97 60 offers you the additional option of using access control functions and managing up to 2,000 employees.

9700-K6	Option package 97 20	Option package 97 40	Option package 97 60
<b>Device software</b>			
B-client HR30	●	●	●
<b>Reader</b>			
Multi RFID reader (LEGIC/MIFARE) with BLE	●	●	●
HID iClass SE proximity reader	○	○	○
Other RFID readers <sup>2</sup>	○	○	○
Biometric reader for 500/3,000/5,000 persons <sup>3</sup>	○	○	○
Magnetic stripe reader <sup>2</sup>	○	○	○
Barcode CCD scanner	○	○	○
<b>Host interface</b>			
10/100/1,000 Ethernet interface (IPv4, IPv6)	●	●	●
WLAN	○	○	○
<b>Power supply</b>			
Power over Ethernet	●	●	●
24 V DC <sup>4</sup>	○	○	○
100 V – 230 V AC <sup>4</sup>	○	○	○
Uninterruptable power supply	○	○	○
<b>Options</b>			
Door control	○	○	●
Data encryption	●	●	●
CardLink / AoC / DoC	○	●	●
Camera system <sup>3</sup>	○	○	○
Mobile Access – booking with a smartphone	○	●	●
<b>Storage options</b>			
200 persons	●	–	–
1,000 persons	○	●	–
2,000 persons	○	○	●
10,000 persons	○	○	○
<b>Design</b>			
Docking station	●	●	●
Elastic protective frame	○	○	○
Increased class of protection IP54	○	○	○
Flush-mounted housing	○	○	○
Mounting plate	○	○	○

**Note:** The effectively available scope of product functions depends on the system context in which the product is used.

Standard ●  
Option ○  
Not possible –

### Our Sustainability Commitment

dormakaba is committed to foster a sustainable development along our entire value chain.

In order to give quantified disclosures of a product's environmental impact and its ecological footprint, dormakaba provides Environmental Product Declarations (EPDs). Please download the EPD and read more about our sustainability commitment here or use the QR code provided.



### Technical specification

- Data recording terminal with docking station
- Freescale i.MX6Dual processor
- 7" PCAP touchscreen  
800 x 480 pixels
- dormakaba-specific Android
- 2 GB RAM, 8 GB eMMC Flash
- Audio function and optional camera
- Proximity sensor for increased energy efficiency
- Standby mode

### Power supply

- Power over Ethernet (IEEE 802.3at)
- Power class 0 (0.44–12.95 W)
- USV for up to 30 minutes of operation/200 bookings

### Environment

- Ambient temperature: -5 °C to +45 °C
- Relative humidity: 5% to 85% (non-condensing)
- Protection class according to IEC 60529: IP20/IP54 depending on version

### Housing

- Robust plastic housing with wall mounting plate

### Dimensions (W x H x D) without mounting plate

- 264 mm x 207 mm x 65/96 mm (main device)
- 264 mm x 268 mm x 65/105 mm (with add-on housing)

You can find further details and order information in the corresponding dormakaba catalogues or system descriptions.

- 1 Optional fitting with a PCB based on the selected power supply, interface and/or digital I/Os.
- 2 Installation is done in base housing upon order and cannot be changed later.
- 3 Specification of the feature when ordering the product. Changed version only possible by exchanging the terminal.
- 4 In case of a later change, the exchange of the docking station is required.

WN 05521151532

Subject to change without notice.

© 2023 dormakaba. Version 08/2023



**Any questions? We will be happy to assist you.**