

# QDB200 Deadbolt



## Features

- **SmartKey™ flexibility.** An available re-key system to permit re-keying the lock without having to change or remove the product from the door, and an available key control function make the QDB200 series more versatile and convenient for use and maintenance.
- **Greater security.** Constructed with a full 1" steel throw bolt and hardened steel roller pin, two ball bearings, and free-spinning cylinder collar, QDB200 series deadbolts resist saw, drill, and wrench attacks.
- **Easy to retrofit.** Choose deadbolts with a SFIC option or keep your existing small format cores and use them with QDB200 series products. Standard door preparation makes retrofit quick and easy.
- **Flexible installation.** Compartmentalized packaging makes QDB200 deadbolts easier to install, and an adjustable backset deadbolt latch gives you greater flexibility at the point of installation.
- **Additional security features.** Depending on your application, available options like hurricane compliance can add an additional layer of reliability and security.
- **Short lead time.** Our QDB200 series deadbolts are available for immediate shipment.

### More features for added security

QDB200 series Grade 2 deadbolts have more built-in features for attack resistance. In addition to quality materials and construction, we added components to combat saw, drill, and wrench attacks. When you're choosing a deadbolt for light commercial applications, choose the name more people trust for their security.

The QDB200 series, makes it easy to order, customize, install, and maintain your standard-duty deadbolt for a wide range of applications.

### Versatility and convenience

With a wide range of available features, including re-key flexibility and an adjustable backset deadbolt latch, the QDB200 series deadbolts make installation, customization, and maintenance quick and easy.

### Backed by leading warranties

The QDB200 series comes with lifetime mechanical and three-year finish warranties.



## QDB200 Heavy duty deadbolt specifications

<b>Certifications</b>	ANSI/BHMA A156.12 Series (1999)—Grade 2 ANSI A117.1 Accessibility Code (ADA compliant) UL/cUL listed (3 hour) for "A" label single door applications (4' by 8') UL10C/UBC 7-2 (1997) positive pressure rated UL10B pressure rated Hurricane Compliant – Miami DADA N.O.A. ADA compliant thumb turn	
<b>Product specifications</b>	Exposed trim: stainless steel with iron forged cylinder guard Door range: 1 3/8" (35mm) – 2" (51mm); service part 8Q00082 spacer rings required for 1 3/8" doors Backset: 2 3/4" (70mm) square standard; 2 3/8" (60mm) available Strike: standard deadbolt strike 1 1/8" (32mm) x 2 3/4" (70mm); other options available Door prep: 2 1/8" (54mm) diameter cross bore Latch bolt: full 1"(25.4mm) throw with hardened steel roller Latch faceplate: 1 1/8" (29mm) x 2 1/4" (57mm) standard; 1" (25.4mm) x 2 1/4" (57mm) available	
<b>Keying</b>	6-pin non-IC brass cylinders 6- or 7-pin SFIC option available Two keys per lockset Keying options include: master keying, grand master keying, construction keying Keyway options include: BF-SFIC "F," SMT-SmartKey™, KW-Kwikset, WE-Weiser, SC-Schlage, GA-Yale, LA-Sargent, LC-Less Cylinder	
<b>Functions</b>	ANSI E0152	QDB280 Single Cylinder
	ANSI E0152	QDB281 Single Cylinder SFIC
	ANSI E0142	QDB282 Double Cylinder
	ANSI E0142	QDB283 Double Cylinder SFIC
	ANSI E0193	QDB284 Inside Turnbolt
		QDB285 Indicator
	ANSI E0172	QDB286 Classroom
	ANSI E0172	QDB287 Classroom SFIC
	ANSI E0152	QDB288 Key Control
<b>Finishes</b>	605: Bright Brass, 613: Oil Rubbed Bronze, 619: Satin Nickel, 625: Bright Chrome, 626: Satin Chrome	
<b>Warranties</b>	Lifetime mechanical, three-year finish (613 carries no finish warranty)	



605: Bright Brass



613: Oil-rubbed  
Bronze



619: Satin Nickel



625: Bright  
Chrome



626: Satin  
Chrome

© dormakaba 2025 Information on this sheet is intended for general use only. dormakaba reserves the right to alter designs and specifications without notice or obligation.

**Any questions? We would be happy to advise you.**

Contact us at: 1-800-523-8483