### dormakaba 🚧

## Basic-XS Compact standard electric strike



# Access at the push of a button


Combined with intercom systems, for example, electric strikes from dormakaba can provide easy-release access to most doors encountered in private, public and commercial premises. They offer pushbutton convenience for effective control of who is allowed into a building and therefore enabling the secure locking of doors in various service duty categories. The new standard electric strike series Basic-XS offers high flexibility for building planning with its ultracompact housing and multi-voltage feature.




#### **Product attributes**

- Multi-voltage 12-24 V AC/DC in one version
- Ultra-compact housing enables installation even in extreme narrow door frames
- Non-handed design for universal installation
- · Radius latch
- · Optional: latch guide

## Basic-XS





Technical data	Basic-XS E, 12-24V AC/DC	Basic-XS with latch guide
Order no.	15112244	15112243
Operating voltage	12 - 24 V AC/DC	12 - 24 V AC/DC
Current	12 V AC: 250 mA 24 V AC: 500 mA 12 V DC: 280 mA 24 V DC: 560 mA	12 V AC: 250 mA 24 V AC: 500 mA 12 V DC: 280 mA 24 V DC: 560 mA
Fail-secure mode	•	•
Mechanical deactivation	•	•
Monitoring contact (RR)	-	-
Non-handed	•	•
Radius latch	•	•
Latch guide	-	•
Material latch/housing	Zamak	Zamak
Operating temperature	−15°C bis +40°C	-15°C bis +40°C
Fire-rated doors	-	-

Housing dimensions	Standard	Housing with latch guide
Height	66 mm	66 mm
Width	16 mm	20,1 mm
Depth	25,5 mm	25,5 mm

Subject to technical modifications

WN 05434851532 11/21. Subject to technical modifications