

The Self-Closing Patch Fitting

dormakaba 



UNIVERSAL Motion

For silence and constant temperatures

Real team work with new technology.

UNIVERSAL Motion shows real teamwork. The door always closes gently and thus ensures silence and constant temperature. A patch fitting with integrated self-closing function is not just convenient but also efficient:

The hydraulic technology proves its advantage without requiring a power supply and any visible mechanism. UNIVERSAL Motion is like a reliable employee with intrinsic values: the space-saving technology is integrated in the compact bottom patch fitting.



UNIVERSAL Motion

Eight reasons for the one.

- **Completely smart.** In UNIVERSAL Motion, the door closing function is integrated in a compact, well-shaped unit. A subtly functional design.
- **Almost invisible.** What looks like a patch fitting manages the closing of doors by itself. An additional floor spring is not required.
- **Clear savings.** Less effort and cost-efficient. You need only two fittings for the self-closing swing door: UNIVERSAL Motion and PT 20.
- **Comfortable function.** The door closes softly by itself. The hydraulic door movement is achieved simply in the fitting – without extra installation, without power supply.
- **Simple installation.** UNIVERSAL Motion consists of very few parts. The glass door is clamped in the fitting. No prior changes to the floor are required.
- **For the existing building.** Retrofitting is clearly simpler than before. The floor need not be sawn nor milled beforehand.
- **Simple positioning.** The material and composition of the floor are not critical factors. You need to place only four vertical bores for the bottom pivot bearing.
- **Different surface finishes.** The dormakaba colour palette creates systematic diversity. The colour spectrum corresponds to the standard UNIVERSAL fittings. A custom-made colour scheme as per RAL is also possible. Simply matches the contemporary interior.

Technical data:

Glass thickness:	10 + 12 mm
Door width:	max. 1,000 mm
Door weight:	max. 100 kg
Surface finishes:	Stainless steel and aluminum
Variants:	With / without 90° door held open



dormakaba
International Holding AG
 Hofwissenstrasse 24
 CH-8153 Rümlang
 T +41 44 818 90 11
info@dormakaba.com
www.dormakaba.com