

# E-Plex 5700

## Electronic lock



E-Plex 5700 series of locks creates a range of access control solutions. They are ideal for cost effective access control or augmenting an existing access control system allowing you to utilize existing credentials and infrastructure.

Quick and easy to install and maintain, the E-Plex 5700 Series can function in both wireless or offline modes using dormakaba's Keyscan Aurora Access Control software platform.

The complementary Keyscan LUNA Access Management Software platform is recommended for small offline only installations that are ideal for small business.

Both support PIN codes and can also be used as a 'stand-alone' access solution through a facility.

The E-Plex 5700 model supports 125kHz standard security "prox" credential formats. Also available in narrow stile model (E-Plex 3700)

### Lock function customization

Locks are easily customized on site via keypad to work as various BHMA lock functions, eliminating the requirement to stock multiple locks for different applications. Built-in options include: Entry, Privacy, and Residence lock, (thumbturn required for privacy and residence functions)

### Features and benefits

- **Programming:**
  - Keyscan Aurora software: wireless or offline (requires M-Unit handheld)
  - Keyscan LUNA software: offline only (requires M-Unit)
  - Keypad: via keypad with LearnLok feature
- **Ease of installation:** No wire to or through the door
- **Number of Users** (full system):
  - Keyscan Aurora: Up to 45,000
  - Keyscan LUNA: Up to 10,000
  - E-Plex Enterprise: Up to 3,000
  - Stand-alone: Up to 300 access codes (LearnLok™)
  - Locks support up to 3,000 users per lock and an audit trail of up to 30,000 events

### Scheduling:

- **Access schedules** – Up to 16 different access schedules can be programmed into lock
- **Holiday / Vacation** – Up to 32 different holiday / vacation blocks can be programmed into lock

### Handing:

- Non-handed, pre-assembled for left-hand door installations—easily changed in the field
- Key override
- Key-in-lever cylinders, small format interchangeable cores, large format removable cores

**Three operation modes:**

- PIN only, card only or PIN + card access per access schedule
- Lockout
- Passage – can be toggled on/off or pre-programmed to relock manually or via software

**Passage options:**

- First manager in (or privileged user)
- Automatically according to access schedules



**Authority levels:** Six different levels

allow who has access to specific lock functions, including:

- Master level – Performs all set-up and programming functions
- Manager level – Administers common programming functions
- Access user level – Entry granted with valid credential(s)
- Service level – PIN-only credential for single event or up to four-day access, programmable in advance; no expiry for "Super" Service user
- Guest level – 1-365 day durations
- Maintenance level—No access is granted, but information can be uploaded/downloaded to/from the lock with handheld unit

**User parameters**

- Pin length – Adjustable to accept 4 to 8 digits
- Anti-tamper lockout – Adjustable from 3 to 9 invalid attempts with an adjustable period of 0 to 90 seconds
- Relock time – Adjustable from 2 to 20 seconds
- Manually toggled on / off at lock

**Cylindrical dimensions****Mortise dimensions**

## Specifications

<b>Construction</b>	Extra heavy-duty lockset, solid cast housing, and solid cast lever or thumbturn wear tested for extensive use in indoor and outdoor applications
<b>Numeric keypad</b>	Vandal resistant, solid metal pushbuttons
<b>Handing</b>	Cylindrical and E-Plex Mortise—Non-handed, pre-assembled for left-hand door installations—easily changed in the field Exit Trim—Non-handed
<b>Backset</b>	Cylindrical—23/4" (70 mm), 23/8" (60 mm) Mortise—23/4" (70 mm) Exit Trim—Varies by exit device type
<b>Latch</b>	Cylindrical—1/2" (13 mm) latch, 3/4" (19 mm) latch (optional) with three-hour UL/ULC fire rating Mortise—3/4" (19 mm) latch, 1" (25 mm) deadbolt (optional).
<b>Minimum stile</b>	5" (127 mm)
<b>Weight</b>	Cylindrical—9.5 lbs. (4.30 kg) Exit Trim—9.5 lbs. (4.30 kg) Mortise—11.5 lbs. (5.20 kg)
<b>Universal key-in-lever cylinders</b>	Includes Kaba 1599 6-pin cylinder (prepped to Kaba 90 or Schlage "C" Keyway, keyed different) and tailpieces for compatibility with: Abloy 5277 Corbin Russwin 2000-03 Marks Abloy 5477 Kaba 1539 Medeco 20W200H1 Arrow C100 Kaba 1599 Sargent 10 Line ASSA 65611 Kaba Gemini 4730 Schlage 23-001 ASSA 65691 Kaba Peaks 1099 Schlage Primus 20-760 Australian: Kaba expert 107K5, Boyd KC286 European: Quattro S/Expert, AP2 (5 and 6-pin)
<b>Interchangeable cores</b>	Small format Best and equivalents (6 or 7-pin length)
<b>Removable cores</b>	Large format ASSA, Medeco, Yale, Abloy (5 or 6-pin), Corbin Russwin, Schlage, and Sargent
<b>Ease of installation</b>	LectroBolt eliminates wiring to or through the door—no risk of pinched wires
<b>Door preparation</b>	Cylindrical and Exit Trim—ASA 161 (Easily installs on door preparation with two additional through bore holes (wood or metal doors) Mortise—ASA 86 door preparation with two additional through bore holes
<b>Door thickness</b>	Cylindrical—1 3/8" (35 mm) to 2 1/4" (57 mm) Pre-assembled to accommodate doors 1 5/8" (41 mm) to 2" (50 mm) Mortise—1 3/4" (44 mm) to 2 1/4" (57 mm) Pre-assembled to accommodate doors 1 5/8" (41 mm) to 2" (50 mm) Exit Trim—1 3/4" (44 mm) to 2 1/4" (57 mm) Pre-assembled to accommodate doors 1 3/4" (44 mm) to 2 1/8" (54 mm)
<b>Items supplied</b>	Cylindrical and Mortise—Lock assembly, installation manual, template, quick reference guide, operations manual, and required hardware Exit Trim—Lock assembly, installation manual, template, quick reference guide, operations manual, and required hardware. Exit Device and mounting hardware not included.
<b>Additional items supplied with key-in-lever cylinder model only</b>	Cylindrical and Mortise—Universal Kaba 1599 6-pin cylinder with tailpiece, four additional tailpieces, and two nickel silver keys Exit Trim—Universal Kaba 1599 6-pin cylinder with tailpiece, four additional tailpieces, nickel silver keys, and spare cylinder retainer
<b>Accessibility standard</b>	Americans with Disabilities Act (ADA)
<b>Durability</b>	Cylindrical—ANSI/BHMA A156.2, Grade 1 Certification Mortise—ANSI/BHMA A156.13, Grade 1 Certification Exit Trim—ANSI/BHMA A156.3, Grade 1 Certification Electronic—ANSI/BHMA A156.25, Grade 1 Certification
<b>Fire rating</b>	Three-hour UL/ULC fire door rating for "A" labeled doors
<b>Environmental</b>	Indoor/Outdoor Approved Front Housing: -31 °F (-35 °C) to + 151 °F (66 °C) Rear Housing: -31 °F (-35 °C) to + 130 °F (55 °C)
<b>Standard finishes</b>	Satin Chrome 26D (626) housings and levers Black (676) housings with Satin Chrome (626) levers and accents
<b>Optional finishes</b>	Bright Brass 03 (605) housings and levers Satin Brass 04 (606) housings and levers Bright Chrome 026 (625) housings and levers Dark Bronze (744—simulates 10B/613) housings and levers with Satin Brass (606) pushbuttons
<b>Warranty</b>	Three-year warranty from date of installation; built-in warranty counter in lock memory

## Optional software features



E-Plex offline with Keyscan LUNA and M-Unit handheld



E-Plex 5700 offline with Keyscan LUNA and M-Unit handheld



E-Plex Wireless with Keyscan Aurora

Exit device compatibility

- |                                   |                       |                      |
|-----------------------------------|-----------------------|----------------------|
| • Arrow S1250                     | • Dorex 8500R/8500F   | • Sargent 8888       |
| • Arrow S3883F/S3800              | • Dorex 9500PR/9500FR | • Von Duprin 22/22F  |
| • Black & Decker (K-2) QED111/112 | • Dorma 9300/F9300    | • Von Duprin 98/98F  |
| • Cal Royal 9800                  | • Monarch 18R*, F18R* | • Von Duprin 99/99F  |
| • Cal Royal 2200                  | • Precision 21/FL21   | • Von Duprin XP98/99 |
| • Corbin Russwin ED5200/5200A     | • Sargent 2828        | • Yale YME2100/2100  |
| • Detex 1001 BP1                  | • Sargent 3828        | • Yale 7100          |
| • Detex 10/F10 Series             | • Sargent 8810E/8800  |                      |

\*(requires special K-Hub Adapter)

© dormakaba 2025 Information on this sheet is intended for general use only. dormakaba reserves the right to alter designs and specifications without notice or obligation.

Any questions? We would be happy to advise you.  
Contact us at: 1-800-849-8324