

ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804+A2



Owner of the Declaration	dormakaba International Holding GmbH
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-DOR-20250371-CBA1-EN
Issue date	16/07/2025
Valid to	15/07/2030

Floor Spring BTS 80 series dormakaba

www.ibu-epd.com | <https://epd-online.com>



General Information

dormakaba	Floor Spring BTS 80 series								
Programme holder IBU – Institut Bauen und Umwelt e.V. Hegelplatz 1 10117 Berlin Germany	Owner of the declaration dormakaba International Holding GmbH DORMA Platz 1 58256 Ennepetal Germany								
Declaration number EPD-DOR-20250371-CBA1-EN	Declared product / declared unit 1 piece of the product: Floor Spring BTS 80 series, consisting of the following items: <ul style="list-style-type: none">• Closer body• Cement box• Product packaging								
This declaration is based on the product category rules: Building Hardware products, 01/08/2021 (PCR checked and approved by the SVR)	Scope: This Environmental Product Declaration refers to a Floor Spring BTS 80 series manufactured by dormakaba. The production site is located in Singapore. This declaration covers multiple product variants of dormakaba's BTS 80 V / BTS 80 / BTS 80 VF / BTS 80 EMB / BTS 80 V BF / BTS 80 F and BTS 80 FLB Floor Spring series. The declared results are based on the BTS 80 V, which represents the worst-case scenario. The data represents the year 2024. The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences. The EPD was created according to the specifications of EN 15804+A2. In the following, the standard will be simplified as <i>EN 15804</i> .								
Issue date 16/07/2025	Verification <table><tr><td colspan="2">The standard EN 15804 serves as the core PCR</td></tr><tr><td colspan="2">Independent verification of the declaration and data according to ISO 14025:2011</td></tr><tr><td><input type="checkbox"/></td><td>internally</td></tr><tr><td><input checked="" type="checkbox"/></td><td>externally</td></tr></table>	The standard EN 15804 serves as the core PCR		Independent verification of the declaration and data according to ISO 14025:2011		<input type="checkbox"/>	internally	<input checked="" type="checkbox"/>	externally
The standard EN 15804 serves as the core PCR									
Independent verification of the declaration and data according to ISO 14025:2011									
<input type="checkbox"/>	internally								
<input checked="" type="checkbox"/>	externally								
Valid to 15/07/2030									
 Dipl.-Ing. Hans Peters (Chairman of Institut Bauen und Umwelt e.V.)	 Dr.-Ing. Wolfram Trinius, (Independent verifier)								

Product

Product description/Product definition

The door closer technology is recessed in the floor. The BTS 80 floor concealed door closer system with its product variants BTS 80 V (with closing force adjustment), BTS 80 VF (for fire and smoke doors with closing force adjustment), BTS 80 EMB (with electro-hydraulic hold open function), BTS 80 FLB (with free swing function) and accessories allows adaptation to different door designs and functions.

- EN 1154
- EN 1155
- EN 1158
- ANSI A 156.4
- ANSI A 156.15

The CE marking takes into account the proof of conformity with the respective harmonized standards based on the legal provisions above.

Application

The Floor Spring BTS 80 series are designed for single and double acting doors of various sizes and materials. The BTS 80 is ideal for fire/life safety applications, with an electrically controlled hold open function that can also support privacy use when paired with a maintained control switch. It is applicable for following:

- Schools and Universities
- Hospitals and Healthcare Facilities
- Airports and Transportation Hubs
- Government and Public Buildings
- Commercial Offices
- Hotels and Hospitality
- Shopping Centres and Retail Spaces

Technical Data

The Floor Springs have the following technical properties:

Model variants	BTS 80 / BTS 80 V	BTS 80 VF	BTS 80 V BF	BTS 80 F / BTS 80 EMB	BTS 80 FLB
Closing force/door width					
≤ 1100 mm	EN 4			EN 4	EN 4
≤ 1250 mm	EN 5			EN 5	EN 5
≤ 1400 mm	EN 6			EN 6	EN 6
950 - 1400 mm		EN 3-6	Size 1 - 4		
DIN L (opening angle max. 180°)	• 1)	•	• 1)	•	•
DIN R (opening angle max. 180°)	• 1)	•	• 1)	•	•
Double-action door (opening angle max. 175°)	• 1) 2)	• 1) 2)	• 1) 2)	• 1) 2)	—
Delayed closing	•	—	•	—	—
Fail-safe 0–180°	—	—	—	—	•
Latching action continuously adjustable using valve	—	•	—	•	—

- yes ○ in preparation – no

1) Max. opening angle of the floor spring is 175°

2) Not approved for fire doors in Germany

Performance data of the product with respect to its characteristics in accordance with the relevant technical provision which can be applied are mentioned above.

Base materials/Ancillary materials

The major material composition including the packaging of the product is listed below:

Name	Value	Unit
Steel	90	%
Packaging	4	%
Zinc	2	%
Lubricant	2	%
Brass	1	%
Others	1	%

The product includes partial articles which contain substances listed in the Candidate *List of REACH Regulation 1907/2006/EC* (date: 25.01.2025) exceeding 0.1 percentage by mass: yes

- Lead (Pb): 7439-92-1 (CAS-No.) is included in some of the alloys used. The concentration of lead in each individual alloy does not exceed 4% (by mass).

The *Candidate List* can be found on the ECHA website address: <https://echa.europa.eu/de/home>.

Reference service life

The reference service life of the Floor Spring BTS 80 series is about 20 years, depending on the application and frequency of use. For maintenance, retrofitting, and renewals suitable spare parts are available. The Floor Spring is tested and certified to EN 1154, meaning they are designed to withstand a minimum of 500,000 cycles. The ANSI version is tested and certified to BHMA A156.4, meaning they are designed to withstand a minimum of 1,500,000 cycles.

LCA: Calculation rules

Declared Unit

The declared unit is 1 piece of the product: Floor Spring BTS 80 series, including packaging:

Name	Value	Unit
Declared unit	1	piece/product
Mass of declared Product without Packaging	7.39	kg
Mass of Packaging	0.29	kg
Total mass of declared product	7.68	kg

System boundary

The type of EPD is: cradle to gate with options, modules C1–C4, and module D (A1–A3 + C + D and additional modules: A4+ A5)

Production - Module A1-A3

The product stage includes: — A1, raw material extraction, processing and mechanical treatments, processing of secondary material input (e.g. recycling processes), — A2, transport to the manufacturer, — A3, manufacturing and assembly including provision of all materials, products and

energy, as well as waste processing up to the end-of-waste state.

Construction stage - Modules A4-A5

The construction process stage includes:

— A4, transport to the building site; — A5, installation into the building; including provision of all materials, products and energy, as well as waste processing up to the end-of-waste state or disposal of final residues during the construction process stage.

End-of-life stage— Modules C1-C4 and D

The end-of-life stage includes: — C1, de-construction, demolition; — C2, transport to waste processing; — C3, waste processing for reuse, recovery and/or recycling; — C4, disposal; including provision and all transport, provision of all materials, products and related energy and water use. Module

D (Benefits and loads beyond the system boundary) includes: — D, recycling potentials, expressed as net impacts and benefits.

Geographic Representativeness

Land or region, in which the declared product system is manufactured, used or handled at the end of the product's lifespan: Global

Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to *EN 15804* and the building context, respectively the product-specific characteristics of performance, are taken into account. Background database: GaBi, SP40.

LCA: Scenarios and additional technical information

Characteristic product properties of biogenic carbon

Name	Value	Unit
Biogenic carbon content in product	-	kg C
Biogenic carbon content in accompanying packaging	0.11	kg C

Singapore is considered for A3.

Note: 1 kg of biogenic carbon is equivalent to 44/12 kg of CO₂.

Transport to the building site (A4)

Name	Value	Unit
Litres of fuel	0.00276	l/100km
Capacity utilisation (including empty runs)	55	%
Transport distance (for scaling)	100	km
Transport distance via truck (from dormakaba to harbor)	300	km
Transport distance via ship (from harbor to harbor)	10000	km

The product is transported via truck and ship. The product is stored in the dormakaba logistic center in Wuppertal. The main distribution regions are Asia, US and Europe with the calculated transport distances. In order to allow scaling to a specific point of installation 100 km are declared as well.

Installation into the building (A5)

Name	Value	Unit
Waste packaging (paper / technical documentation)	0.29	kg

Reference service life

Name	Value	Unit
Life Span according to the manufacturer	20	a

End of life (C1-C4)

The product dismantling from the building is done manually without environmental burden.

Transport to waste management is 50 km

Name	Value	Unit
Collected separately waste type	7.4	kg
Recycling	7.38	kg
Energy recovery	0.01	kg

The product is disassembled in a recycling process. Material recycling is then assumed for metals. The plastic components are assumed to be incinerated with energy recovery. The minor proportions of residues arising from the recycling process are landfilled. Region for the End of Life is: Global.

Reuse, recovery and/or recycling potentials (D), relevant scenario information

Name	Value	Unit
Recycling	100	%

The collection rate is 100 %.

LCA: Results

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE OR INDICATOR NOT DECLARED; MNR = MODULE NOT RELEVANT)

Product stage			Construction process stage		Use stage							End of life stage				Benefits and loads beyond the system boundaries
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	MND	MND	MNR	MNR	MNR	MND	MND	X	X	X	X	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A2: 1 piece Floor Spring BTS 80 series

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
GWP-total	kg CO ₂ eq	1.55E+01	5.2E-01	4.1E-01	0	3.23E-02	6.3E-01	0	-2.08E+00
GWP-fossil	kg CO ₂ eq	1.6E+01	5.08E-01	1.03E-02	0	3.09E-02	6.29E-01	0	-2.08E+00
GWP-biogenic	kg CO ₂ eq	-4.42E-01	1.22E-02	3.99E-01	0	1.43E-03	8.39E-04	0	-4.24E-03
GWP-luluc	kg CO ₂ eq	1.49E-02	1.13E-05	6.74E-06	0	7.36E-07	3.56E-05	0	-5.85E-04
ODP	kg CFC11 eq	1.26E-11	5.08E-17	7.39E-17	0	3.26E-18	3.17E-16	0	-2.77E-13
AP	mol H ⁺ eq	5.77E-02	9.51E-03	1.15E-04	0	3.09E-05	1.12E-04	0	-5.54E-03
EP-freshwater	kg P eq	3.47E-05	1.12E-07	1.44E-08	0	6.62E-09	5.06E-08	0	-2.73E-06
EP-marine	kg N eq	1.44E-02	2.53E-03	4.14E-05	0	9.84E-06	2.53E-05	0	-9.49E-04
EP-terrestrial	mol N eq	1.56E-01	2.77E-02	5.17E-04	0	1.09E-04	5.11E-04	0	-9.91E-03
POCP	kg NMVOC eq	4.34E-02	7.06E-03	1.1E-04	0	2.78E-05	7E-05	0	-3.55E-03
ADPE	kg Sb eq	1.2E-03	1.42E-08	1.17E-09	0	9.27E-10	4.35E-09	0	-2.37E-04
ADPF	MJ	2.19E+02	6.68E+00	1.29E-01	0	4.38E-01	2.92E-01	0	-2.4E+01
WDP	m ³ world eq deprived	1.96E+00	9.55E-04	5.08E-02	0	6.06E-05	6.44E-02	0	-2.32E-01

GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources; WDP = Water (user) deprivation potential

RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A2: 1 piece Floor Spring BTS 80 series

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
PERE	MJ	4.47E+01	2.15E-02	3.49E+00	0	1.38E-03	8.14E-02	0	-2.51E+00
PERM	MJ	3.47E+00	0	-3.47E+00	0	0	-5.52E-03	0	0
PERT	MJ	4.82E+01	2.15E-02	2.35E-02	0	1.38E-03	7.59E-02	0	-2.51E+00
PENRE	MJ	2.19E+02	6.69E+00	1.29E-01	0	4.39E-01	5.73E-01	0	-2.4E+01
PENRM	MJ	2.81E-01	0	0	0	0	-2.81E-01	0	0
PENRT	MJ	2.2E+02	6.69E+00	1.29E-01	0	4.39E-01	2.92E-01	0	-2.4E+01
SM	kg	6.85E+00	0	0	0	0	0	0	0
RSF	MJ	0	0	0	0	0	0	0	0
NRSF	MJ	0	0	0	0	0	0	0	0
FW	m ³	8.02E-02	3.87E-05	1.2E-03	0	2.48E-06	1.54E-03	0	-7.64E-03

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

RESULTS OF THE LCA - WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A2: 1 piece Floor Spring BTS 80 series

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
HWD	kg	3.34E-07	6.53E-10	1.91E-10	0	4.26E-11	1.11E-09	0	-1.39E-06
NHWD	kg	4.99E-01	6.84E-04	1.28E-02	0	4.49E-05	6.54E-02	0	1.16E-01
RWD	kg	7.86E-03	7.31E-06	6.8E-06	0	4.71E-07	1.08E-05	0	-9.39E-04
CRU	kg	0	0	0	0	0	0	0	0
MFR	kg	0	0	0	0	0	7.15E+00	0	0
MER	kg	0	0	0	0	0	0	0	0
EEE	MJ	0	0	6.2E-01	0	0	1.17E+00	0	0
EET	MJ	0	0	1.12E+00	0	0	2.68E+00	0	0

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EET = Exported thermal energy

RESULTS OF THE LCA – additional impact categories according to EN 15804+A2-optional: 1 piece Floor Spring BTS 80 series

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
PM	Disease incidence	7.36E-07	1.59E-07	6.36E-10	0	1.63E-10	1.43E-09	0	-7.49E-08
IR	kBq U235 eq	9.71E-01	1.05E-03	1.05E-03	0	6.73E-05	9.77E-04	0	-1.18E-01
ETP-fw	CTUe	7.54E+01	4.73E+00	6.14E-02	0	3.11E-01	1.1E-01	0	-4.74E+00
HTP-c	CTUh	8.15E-09	8.91E-11	3.25E-12	0	5.84E-12	9.48E-12	0	2.49E-09
HTP-nc	CTUh	2.95E-07	4E-09	1.41E-10	0	2.5E-10	9.6E-10	0	2.45E-07
SQP	SQP	9.01E+01	1.75E-02	3.43E-02	0	1.13E-03	8.74E-02	0	-1.14E+00

PM = Potential incidence of disease due to PM emissions; IR = Potential Human exposure efficiency relative to U235; ETP-fw = Potential comparative Toxic Unit for ecosystems; HTP-c = Potential comparative Toxic Unit for humans (cancerogenic); HTP-nc = Potential comparative Toxic Unit for humans (not cancerogenic); SQP = Potential soil quality index

Disclaimer 1 – for the indicator “Potential Human exposure efficiency relative to U235”. This impact category deals mainly with the eventual impact of low-dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure or radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, radon and from some construction materials is also not measured by this indicator.

Disclaimer 2 – for the indicators “abiotic depletion potential for non-fossil resources”, “abiotic depletion potential for fossil resources”, “water (user) deprivation potential, deprivation-weighted water consumption”, “potential comparative toxic unit for ecosystems”, “potential comparative toxic unit for humans – cancerogenic”, “Potential comparative toxic unit for humans - not cancerogenic”, “potential soil quality index”. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high as there is limited experience with the indicator.

This EPD was created using a software tool.

References

EN 1154

EN1154: 1996 / A1:2002 / AC:2006;
Building hardware Controlled door closing devices
Requirements and test methods

EN 1155

EN 1155-2003-04; Building hardware – Electrically -powered hold -open devicesfor swing doors Requirements and test methods (includes amendment A1:2002); German version /EN 1155:1997+A1:2002

EN 1158

EN 1158-2003-04; Building hardware – Door coordinator devices –Requirementsand test methods (includes amendment A1:2002); Germanversion /EN 1158:1997 + A1:2002

EN 11554

DIN EN ISO 11554:2017-12;
Optics and photonics - Lasers and laser-related equipment - Test methods for laser beam power, energy and temporal characteristics (ISO 11554:2017); German version EN ISO 11554:2017

EN 15804

EN 15804+A2:2019+AC:2021,
Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products

ANSI/BHMA A156.4

ANSI/BHMA A156.4:2019, Standard for Door Controls – Closers

ANSI/BHMA A156.15

American National Standard for Release Devices – Electrically Powered Hold-Open Devices for Swinging Doors

ECHA

European Chemical Agency

ISO 14025

DIN EN ISO 14025:201110, Environmental labels and declarations — Type III environmental declarations — Principles and procedures

REACH

Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Further References

IBU 2021

General Instructions for the EPD programme of Institut Bauen und Umwelt e.V. Version 2.0, Berlin: Institut Bauen und Umwelt e.V., 2021. www.ibu-epd.com

GaBi

Sphera Solutions GmbH
Gabi Software System and Database for Life Cycle Engineering 19922020
Version 10.0.0.71
University of Stuttgart
Leinfelden-Echterdingen

GaBi ts documentation

GaBi life cycle inventory data documentation (<https://www.gabisoftware.com/support/gabi/gabidatabase-2020-lcidocumentation/>).

LCA-tool dormakaba

Tool No.: IBU-DOR-202104-LT1-EN.
Developed by Sphera Solutions GmbH

PCR Part A

PCR – Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Project Re-port according to EN 15804+A2:2019,

PCR Part B

PCR – Part B: Requirements on the EPD for Building Hardware



Publisher

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com



Programme holder

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com



Author of the Life Cycle Assessment

dormakaba International Holding GmbH
DORMA Platz 1
58256 Ennepetal
Germany

+49 2333 793-0
info.de@dormakaba.com
www.dormakaba.com



Owner of the Declaration

dormakaba International Holding GmbH
DORMA Platz 1
58256 Ennepetal
Germany

+49 2333 793-0
info.de@dormakaba.com
www.dormakaba.com