

ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804+A2

Owner of the Declaration	dormakaba International Holding GmbH
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-DOR-20220169-CBA6-EN
Issue date	29.11.2022
Valid to	28.11.2027

Manual Revolving Door KTV M Dormakaba

www.ibu-epd.com | <https://epd-online.com>



General Information

Dormakaba

Programme holder

IBU – Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Declaration number

EPD-DOR-20220169-CBA6-EN

This declaration is based on the product category rules:

Automatic doors, automatic gates, and revolving door systems,
01.08.2021
(PCR checked and approved by the SVR)

Issue date

29.11.2022

Valid to

28.11.2027



Dipl.-Ing. Hans Peters
(Chairman of Institut Bauen und Umwelt e.V.)



Florian Pronold
(Managing Director Institut Bauen und Umwelt e.V.)

Manual Revolving Door KTV M

Owner of the declaration

dormakaba International Holding GmbH
DORMA Platz 1
58256 Ennepetal
Germany

Declared product / declared unit

The declaration represents one manual revolving door, consisting of four (4) door leaves with a diameter of 2200 mm and a height of 2200 mm, consisting of the following items:

- Drum wall
- Canopy construction
- Door wings
- Turnstile fittings
- Electric accessories / sensors
- Floor ring
- Product packaging

Scope:

This EPD is a specific product declaration for the KTV M manual revolving door. The underlying life cycle assessment is based on the entire life cycle of this specific revolving door. The KTV M is manufactured at the dormakaba production facility in Sofia, Bulgaria.
Data represents the year 2022.

The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

The EPD was created according to the specifications of EN 15804+A2. In the following, the standard will be simplified as *EN 15804*.

Verification

The standard EN 15804 serves as the core PCR	
Independent verification of the declaration and data according to ISO 14025:2011	
<input type="checkbox"/>	internally
<input checked="" type="checkbox"/>	externally



Dr.-Ing. Wolfram Trinius,
(Independent verifier)

Product

Product description/Product definition

The KTV revolving door range is designed for installation in entrance areas where interior environmental control coupled with elegant aesthetics are desired.

dormakaba KTV revolving doors hold back noise, dust and dirt, reliably protect employees near the entrances from drafts, and help to keep the heating costs down. They also allow for a smooth flow of traffic.

Manual revolving doors (KTV M) are activated and rotated by the user pushing a handle. They offer the following benefits:

- Extensive design flexibility in terms of planning and technical requirements
- Visually, technically and economically the ideal application
- Optimization of the building energy balance
- Efficient noise protection
- Tailored integrated application combining industrial engineering precision and assured quality.

For placing the product on the market in the European Union/European Free Trade Association (EU/EFTA) (with the exception of Switzerland), the following legal provisions apply:

- 2011/765/ EU ROHS3 Directive

as well as the harmonized norms based on these provisions:

- DIN EN ISO 13849-1: Safety of machinery - Safety-related parts of control systems - Part 1: General principles for design.
- DIN EN ISO 12100: Safety of machinery - Basic concepts - Risk assessment and risk reduction.
- DIN EN 16005: Power operated pedestrian doorsets - Safety in use - Requirements and test methods.
- DIN EN 60335 - 1: Safety of household and similar electrical appliances. Part 1: General requirements.
- EN 60335-2-103: Household and similar electrical appliances. Safety. Particular requirements for drives for gates, doors and windows.

The CE- marking takes into account the proof of conformity with the respective harmonized norms based on the legal provisions above. For the application and use, the respective national provisions apply.

In addition to the harmonized standards, the following national standards have also been applied and complied with:

- DIN 18650-1: Powered pedestrian doors. Part 1: Product requirements and test methods.
- DIN 18650-2: Powered pedestrian doors. Part 2: Safety at powered pedestrian doors.

Application

Manual revolving doors may be used to provide a comfortable entry and exit in many applications in the facade of or within a building.

Typical applications include:

- Office / commercial buildings
- Airports
- Public buildings
- Hospitals
- Hotels

Manual revolving doors are used to control the pedestrian flow in combination with an optimal thermal separation of the inside and outside climates during normal use.

KTV M revolving doors can optionally be equipped with:

- 3- or 4-wing design
- Glazed drum walls or with metal paneling
- Additional curved sliding doors in front of the entrance to act as night shields

Observance of the applicable regulations and standards guarantees the highest level of pedestrian safety.

Technical Data

The following technical options are available for the KTV M:

Name	Availability
Drum wall glass body impact resistance according to DIN 52290, class A 1	included
Air curtain	optional
Night shield	optional
Boolfold wings	optional
Stainless steel cladding	optional

Base materials/Ancillary materials

For the main product components: One manual revolving door, consisting of four (4) door leaves, with a diameter of 2200mm and a height of 2200mm, the product composition of the KTV M including packaging is the following:

Name	Value	Unit
Glass	45	%
Aluminium	33	%
Steel	5	%
Stainless Steel	5	%
Zinc	2	%
Plastics	3	%
Paper	3	%
Others	4	%

Performance data of the product with respect to its characteristics in accordance with the relevant technical provision which can be applied are mentioned above.

The KTV M includes partial articles which contain substances listed in the Candidate List of REACH Regulation 1907/2006/EC (date: 17.01.2022) exceeding 0.1 percentage by mass: yes

- Lead (Pb): 7439-92-1 (CAS-No.) is included in some of the alloys used. The concentration of lead in each individual alloy does not exceed 4.0% (by mass).

The Candidate List can be found on the ECHA website address: <https://echa.europa.eu/de/home>

Reference service life

The reference service life of dormakaba's automatic revolving doors is about 20 years, depending on the application and frequency of use. This is consistent with approximately 2.000.000 million cycles over the door's service life.

LCA: Calculation rules

Declared Unit

The declared unit is 1 piece of the product KTV M:

Name	Value	Unit
Declared unit for revolving door system*	4.84	m ²
Mass of the entire system (excl. packaging)	641.9	kg
Grammage of the components	132.62	kg/m ²
Dimensions for revolving door, diameter	2200	mm
Dimensions for revolving door, height	2200	mm

* Area represents the cross-sectional area of the door, which is designed to fit in an opening of 2200 mm wide by 2200 mm high.

System boundary

The type of EPD is: cradle to gate with options, modules C1–C4, and module D (A1–A3 + C + D and additional modules: A4 + A5 + B6)

Production - Module A1-A3

The product stage includes:

- A1, raw material extraction, processing and mechanical treatments, processing of secondary material input (e.g. recycling processes),
- A2, transport to the manufacturer,
- A3, manufacturing and assembly including provision of all materials, products and energy, as well as waste processing up to the end-of-waste state.

Construction stage - Modules A4-A5

The construction process stage includes:

- A4, transport to the building site;

— A5, installation into the building; including provision of all materials, products and energy, as well as waste processing up to the end-of-waste state or disposal of final residues during the construction process stage.

Use stage - Module B6

The use stage related to the operation of the building includes:

- B6, operational energy use

End-of-life stage– Modules C1-C4 and D

The end-of-life stage includes:

- C1, de-construction, demolition;
- C2, transport to waste processing;
- C3, waste processing for reuse, recovery and/or recycling;
- C4, disposal; including provision and all transport, provision of all materials, products and related energy and water use. Module D (Benefits and loads beyond the system boundary) includes:
- D, recycling potentials, expressed as net impacts and benefits.

Geographic Representativeness

Land or region, in which the declared product system is manufactured, used or handled at the end of the product's lifespan: Germany

Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to *EN 15804* and the building context, respectively the product-specific characteristics of performance, are taken into account. Background database: GaBi, SP40.

LCA: Scenarios and additional technical information

Characteristic product properties of biogenic carbon

Information on describing the Biogenic Carbon Content at factory gate

Name	Value	Unit
Biogenic carbon content in product	12.72	kg C
Biogenic carbon content in accompanying packaging	7.36	kg C

The following technical scenario information is required for the declared modules

Transport to the building site (A4)

Name	Value	Unit
Litres of fuel (per 1 kg)	0.00276	l/100km
Transport distance	100	km
Capacity utilisation (including empty runs)	55	%

The product is transported via truck from the production site in Bulgaria to the European sales markets. The product is stored in the hub in Germany. In order to allow scaling to a specific point of installation 100 km is declared.

Installation into the building (A5)

Name	Value	Unit
Waste packaging (paper and plastic)	24	kg

Reference service life

Name	Value	Unit
Life Span according to the manufacturer	20	a

End of life (C1-C4)

C1: The product dismantling from the building is done manually without environmental burden.

Name	Value	Unit
Collected separately waste type waste type	617	kg
Recycling	314	kg
Energy recovery	10.6	kg
Landfilling	292	kg
Transport to waste management	50	km

The product is disassembled in a recycling process. Material recycling is then assumed for the metals and electromechanics. The plastic components are assumed to be incinerated with energy recovery. Minor proportions of residues arising from the recycling process, and glass/inert materials are landfilled. Region for the End of Life is: Global.

Reuse, recovery and/or recycling potentials (D), relevant scenario information

The collection rate is 100 %.

LCA: Results

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE OR INDICATOR NOT DECLARED; MNR = MODULE NOT RELEVANT)

Product stage			Construction process stage		Use stage							End of life stage				Benefits and loads beyond the system boundaries
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	MND	X	MNR	MNR	MNR	MND	MND	X	X	X	X	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A2: Manual Revolving Door KTV M

Parameter	Unit	A1-A3	A4	A5	B2	C1	C2	C3	C4	D
GWP-total	kg CO ₂ eq	2.71E+03	5.61E+00	3.85E+01	0	0	2.69E+00	7.56E+01	4.46E+00	-1.5E+03
GWP-fossil	kg CO ₂ eq	2.79E+03	5.36E+00	1.09E+01	0	0	2.57E+00	2.78E+01	4.43E+00	-1.5E+03
GWP-biogenic	kg CO ₂ eq	-7.29E+01	2.48E-01	2.76E+01	0	0	1.19E-01	4.78E+01	1.5E-02	-3.68E+00
GWP-luluc	kg CO ₂ eq	1.45E+00	1.28E-04	1E-03	0	0	6.12E-05	2E-03	1.3E-02	-4.91E-01
ODP	kg CFC11 eq	3.25E-10	5.66E-16	1.02E-14	0	0	2.72E-16	1.96E-14	1.64E-14	-1.04E-08
AP	mol H ⁺ eq	1.46E+01	5E-03	1E-02	0	0	3E-03	1.2E-02	3.2E-02	-5.73E+00
EP-freshwater	kg P eq	2.59E-03	1.15E-06	1.82E-06	0	0	5.5E-07	3.06E-06	7.61E-06	-9.18E-04
EP-marine	kg N eq	2.36E+00	2E-03	3E-03	0	0	8.19E-04	3E-03	8E-03	-7.71E-01
EP-terrestrial	mol N eq	2.61E+01	1.9E-02	4.4E-02	0	0	9E-03	5.5E-02	9E-02	-8.36E+00
POCP	kg NMVOC eq	6.41E+00	5E-03	9E-03	0	0	2E-03	9E-03	2.5E-02	-2.44E+00
ADPE	kg Sb eq	5.6E-02	1.61E-07	1.51E-07	0	0	7.71E-08	2.81E-07	3.98E-07	-2.3E-02
ADPF	MJ	3.66E+04	7.6E+01	1.37E+01	0	0	3.65E+01	2.3E+01	5.82E+01	-2.11E+04
WDP	m ³ world eq deprived	4.13E+02	1E-02	4.56E+00	0	0	5E-03	7.77E+00	4.65E-01	-1.23E+02

GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources; WDP = Water (user) deprivation potential)

RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A2: Manual Revolving Door KTV M

Parameter	Unit	A1-A3	A4	A5	B2	C1	C2	C3	C4	D
PERE	MJ	1.24E+04	2.4E-01	2.43E+02	0	0	1.15E-01	4.85E+02	7.62E+00	-9.34E+03
PERM	MJ	7.2E+02	0	-2.4E+02	0	0	0	-4.8E+02	0	0
PERT	MJ	1.32E+04	2.4E-01	2.85E+00	0	0	1.15E-01	5.2E+00	7.62E+00	-9.34E+03
PENRE	MJ	3.6E+04	7.6E+01	1.86E+02	0	0	3.65E+01	4.02E+02	5.82E+01	-2.11E+04
PENRM	MJ	5.51E+02	0	-1.72E+02	0	0	0	-3.79E+02	0	0
PENRT	MJ	3.66E+04	7.6E+01	1.37E+01	0	0	3.65E+01	2.3E+01	5.82E+01	-2.11E+04
SM	kg	1.97E+01	0	0	0	0	0	0	0	0
RSF	MJ	0	0	0	0	0	0	0	0	0
NRSF	MJ	0	0	0	0	0	0	0	0	0
FW	m ³	3.08E+01	4.3E-04	1.08E-01	0	0	2.06E-04	1.84E-01	1.5E-02	-1.79E+01

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

RESULTS OF THE LCA - WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A2: Manual Revolving Door KTV M

Parameter	Unit	A1-A3	A4	A5	B2	C1	C2	C3	C4	D
HWD	kg	4.5E-05	7.38E-09	3.12E-08	0	0	3.54E-09	5.51E-08	8.87E-07	-7.87E-05
NHWD	kg	6.12E+02	8E-03	1.94E+00	0	0	4E-03	3.16E+00	2.93E+02	-3.53E+02
RWD	kg	1.8E+00	8.16E-05	6.46E-04	0	0	3.92E-05	1E-03	6.62E-04	-2.16E+00
CRU	kg	0	0	0	0	0	0	0	0	0
MFR	kg	0	0	0	0	0	0	2.86E+02	0	0
MER	kg	0	0	0	0	0	0	0	0	0
EEE	MJ	4.29E+00	0	6.17E+01	0	0	0	0	0	0
EET	MJ	7.78E+00	0	1.21E+02	0	0	0	0	0	0

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EET = Exported thermal energy

RESULTS OF THE LCA – additional impact categories according to EN 15804+A2-optional: Manual Revolving Door KTV M

Parameter	Unit	A1-A3	A4	A5	B2	C1	C2	C3	C4	D
PM	Disease incidence	1.45E-04	2.82E-08	6.71E-08	0	0	1.35E-08	9.65E-08	3.94E-07	-9.43E-05
IR	kBq U235 eq	3.41E+02	1.2E-02	8.9E-02	0	0	6E-03	1.36E-01	6.8E-02	-4.32E+02
ETP-fw	CTUe	2.04E+04	5.38E+01	6.02E+00	0	0	2.58E+01	9.25E+00	3.32E+01	-8.1E+03
HTP-c	CTUh	4.34E-05	1.01E-09	3.78E-10	0	0	4.86E-10	7.09E-10	4.92E-09	-4.35E-07
HTP-nc	CTUh	3.72E-05	4.33E-08	2.52E-08	0	0	2.08E-08	5.18E-08	5.43E-07	8.96E-06
SQP	SQP	8.4E+03	1.95E-01	3.79E+00	0	0	9.4E-02	6.65E+00	1.21E+01	-8.36E+02

PM = Potential incidence of disease due to PM emissions; IR = Potential Human exposure efficiency relative to U235; ETP-fw = Potential comparative Toxic Unit for ecosystems; HTP-c = Potential comparative Toxic Unit for humans (cancerogenic); HTP-nc = Potential comparative Toxic Unit for humans (not cancerogenic); SQP = Potential soil quality index

Disclaimer 1 – for the indicator IRP This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

Disclaimer 2 – for the indicators ADPE, ADPF, WDP, ETP-fw, HTP-c, HTP-nc, SQP The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

References

DIN 18650-1

DIN 18650-1/: Powered pedestrian doors. Part 1: Product requirements and test methods.

DIN 18650-2

DIN 18650-2/: Powered pedestrian doors. Part 2: Safety at powered pedestrian doors.

DIN EN 16005

DIN EN 16005: Power operated pedestrian doorsets - Safety in use - Requirements and test methods.

DIN 52290

DIN 52290-2: Security glazing; testing the bullet-resistance and classification.

DIN EN 55022

DIN EN 55022: Information technology equipment - Radio disturbance characteristics - Limits and methods of measurement.

DIN EN 60335

DIN EN 60335 - 1: Safety of household and similar electrical appliances. Part 1: General requirements.

DIN EN ISO 9001

DIN EN ISO 9001: Quality management systems.

DIN EN ISO 12100

DIN EN ISO 12100: Safety of machinery - Basic concepts - Risk assessment and risk reduction.

DIN EN ISO 13849-1

DIN EN ISO 13849-1: Safety of machinery - Safety-related parts of control systems - Part 1: General principles for design.

EN 15804

EN 15804+A2: 2019+AC:2021, Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products.

EN 60335-2-103

EN 60335-2-103: Household

and similar electrical appliances. Safety. Particular requirements for drives for gates, doors and windows.

IEC 60335-2-103

IEC 60335-2-103: Household and similar electrical appliances. Safety. Part 2-103: Particular requirements for drives for gates, doors and windows.

ISO 14025

DIN EN ISO 14025:201110, Environmental labels and declarations — Type III environmental declarations — Principles and procedures.

REACH Regulation

REACH Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals.

RoHS 2011/65/EU

RoHS 2011/65/EU, Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment.

European Chemicals Agency (ECHA)

<https://echa.europa.eu/de/home> Further References

IBU 2021

General Instructions for the EPD programme of Institut Bauen und Umwelt e.V.
Version 2.0, Berlin: Institut Bauen und Umwelt e.V., 2021.
www.ibu-epd.com

GaBi ts software

Sphera Solutions GmbH
Gabi Software System and Database for Life Cycle Engineering 1992-2020
Version 10.0.0.71
University of Stuttgart
Leinfelden-Echterdingen

GaBi ts documentation

GaBi life cycle inventory data documentation
(<https://www.gabisoftware.com/support/gabi/gabidatabase-2020-lci-documentation/>).

LCA-tool dormakaba

LCA tool, ENS (doors)
Tool No.: IBU-DOR-202107-LT1-EN
Developed by Sphera Solutions GmbH.

PCR Part A

PCR – Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Project Report according to EN 15804+A2:2019, Version 1.0, Institut Bauen und Umwelt e.V., www.ibu-epd.com.

PCR Part B

PCR – Part B: Requirements on the EPD for Automatic doors, automatic gates and revolving door system, version 08/2021, Institut Bauen und Umwelt e.V., www.ibu-epd.com



Publisher

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com



Programme holder

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com



Author of the Life Cycle Assessment

Sphera Solutions GmbH
Hauptstraße 111- 113
70771 Leinfelden-Echterdingen
Germany

+49 711 341817-0
info@sphera.com
www.sphera.com



Owner of the Declaration

dormakaba International Holding GmbH
DORMA Platz 1
58256 Ennepetal
Germany

+49 2333 793-0
info.de@dormakaba.com
www.dormakaba.com