

Keyscan access control unit features

Access control unit	KC-2A	KC-4A	KC-8A
Doors supported	2 doors	4 doors	8 doors
Reader ports	2	4	8 (2x 4 door panels)
Multi panel compatible	Yes (TCP/IP)	Yes (TCP/IP)	Yes (TCP/IP)
Troubleshooting LED screen	Yes	Yes	Yes
Flash upgradable firmware	Yes	Yes	Yes
Power fail output	Yes	Yes	Yes
Troubleshooting assistance	Onboard LED screen	Onboard LED screen	Onboard LED screen
Input			
Request to exit inputs (supervised)	2	4	8 (4x2)
Door contact inputs	2	4	8 (4x2)
Auxiliary inputs (supervised)	4	4	8 (4x2)
I/O input expansion (with IOCB1616)	Yes	Yes	Yes
Outputs			
Form C auxiliary output relays	2	2	4 (2x2)
Digital auxiliary output relays	4	4	8 (4x2)
IOCB1616 Inputs & Outputs	16	16	16
Capacity			
No. of credential-holders	Up to 100,000	Up to 100,000	Up to 100,000
Transaction buffer	6000	6000	6000
Schedules & groups	512/511	512/511	512/511
Holiday dates	64	64	64
Connectivity			
TCP/IP ready	Built in	Built in	Built in
CMAC	Coming soon	Coming soon	Coming soon
Software Aurora Version	Aurora 2.0.1	Aurora 2.0.1	Aurora 2.0.1

© dormakaba 2026 Information on this sheet is intended for general use only. dormakaba reserves the right to alter designs and specifications without notice or obligation. All trademarks are the property of their respective owners.

Any questions? We would be happy to advise you.

Contact us at: 1.888.539.7226